



TABLA DE CLAROS MÁXIMOS PARA VIGAS RYMSA

VIGA	ARMADO	SEPARACION EN CM.	CARGA SOBREPUESTA EN KG./M2							PESO DEL SISTEMA EN KG/M2 (con capa de compresión de 5 cm.)
			100 kg./m2	150 kg./m2	200 kg./m2	250 kg./m2	300 kg./m2	350 kg./m2	400 kg./m2	
R-15-15	3/33	60.00	5.13	4.85	4.49	4.13	3.81	3.52	3.28	165.50
		70.00	4.90	4.62	4.28	3.93	3.62	3.34	3.11	157.90
		85.00	4.71	4.44	4.10	3.76	3.46	3.19	2.96	152.50
	3/44	60.00	5.23	4.95	4.59	4.23	3.89	3.60	3.35	167.20
		70.00	5.01	4.73	4.38	4.02	3.70	3.42	3.18	159.40
		85.00	4.81	4.54	4.19	3.85	3.54	3.27	3.03	153.70
R-15-20	3/33	60.00	6.34	6.02	5.61	5.18	4.79	4.44	4.14	184.70
		70.00	6.06	5.65	5.26	4.92	4.54	4.20	3.91	173.90
		85.00	5.75	5.27	4.90	4.60	4.33	4.00	3.72	166.20
	3/44	60.00	6.58	6.25	5.82	5.38	4.97	4.61	4.30	186.40
		70.00	6.32	5.99	5.57	5.13	4.74	4.39	4.08	175.40
		85.00	6.09	5.76	5.35	4.92	4.54	4.20	3.91	167.50
R-15-25	3/33	50.00	7.27	6.88	6.44	6.00	5.56	5.17	4.82	204.00
		60.00	6.93	6.40	5.97	5.62	5.82	4.89	4.56	190.00
		70.00	6.51	6.00	5.59	5.25	4.97	4.67	4.35	180.00
		85.00	6.14	5.65	5.26	4.93	4.67	4.44	4.15	172.50
		90.00	5.82	5.34	4.97	4.66	4.40	4.18	3.98	166.70
		100.00	5.54	5.08	4.72	4.42	4.17	3.97	3.78	162.00
	3/44	50.00	7.78	7.42	6.94	6.44	5.97	5.55	5.18	205.70
		60.00	7.47	7.10	6.62	6.13	5.67	5.26	4.91	191.50
		70.00	7.19	6.70	6.24	5.87	5.42	5.02	4.68	181.20
		85.00	6.87	6.31	5.88	5.52	5.19	4.81	4.48	173.60
		90.00	6.51	5.98	5.56	5.22	4.93	4.61	4.29	167.90
		100.00	6.21	5.69	5.28	4.95	4.68	4.44	4.13	162.90
4/44	50.00	7.91	7.54	7.05	6.54	6.06	5.63	5.26	206.60	
	60.00	7.59	7.16	6.69	6.23	5.76	5.34	4.98	192.20	
	70.00	7.29	6.72	6.27	5.89	5.50	5.10	4.75	181.90	
	85.00	6.90	6.34	5.90	5.54	5.24	4.88	4.54	174.10	
	90.00	6.55	6.01	5.59	5.24	4.95	4.68	4.35	168.10	
	100.00	6.24	5.72	5.31	4.98	4.70	4.47	4.19	163.30	